


# MIX-Q370A1

Mini-ITX with 8th/9th Gen Intel® Core™ Processor Family, Max. 65W TDPs, Giga-LAN x 4



## Features

- 8th/9th Gen. Intel® Core™ LGA1151 Processor
- DDR4 DRAM Support, 2666MHz, Max. 32GB
- M.2 Slot (M key- SATA only) x 1, M.2 Slot (E key) x 1
- USB 3.2 Gen 2 Port x 4, USB 2.0 Port x 4
- Intel® LAN 211AT x 3, 219LM for iAMT 12.0 x 1
- SATA 6.0 Gb/s x 2
- PCI-Express [x16] (Gen3) x 1
- ATX Power



## Specifications

System	
Processor	8th/9th Gen. Intel® Core™ LGA 1151 socket Processor (formerly Coffee Lake-S), Max. 65W TDPs
Chipset	Intel® Q370 Express Chipset
Memory	DDR4 2666/2400/2133 MHz SODIMM x 2, Up to 32GB, Non-ECC, Un-buffered Memory, dual-channel memory architecture
I/O Chipset	NCT6793D
Ethernet	Intel® PCIe Gb LAN 219LM x 1, Intel® PCIe Gb LAN i211AT x 3
Audio	Realtek® ALC887 with Amp.
TPM	NPCT650ABBYX TPM2.0 (default: No)
Expansion Slots	PCIe3.0 [x16] x 1 M.2 E-key (22 x 30mm; Support CNVi)
BIOS	256Mbit Flash ROM, AMI BIOS
H/W Monitor	Temperature Monitor on CPU/Chassis, Voltage Monitor on Vcore/5V/12V, Fan Monitor on CPU/Chassis
WatchDog Timer	1~255 steps by software program
Smart Fan Control	CPU Fan/ Chassis Fan
Wake On LAN/ PXE	Yes (WOL / PXE)
Power State	S3, S4, S5
Graphics	
Graphics Chipset	Intel® UHD Graphics
Graphics Multi Display	HDMI+VGA
VGA	Up to 1920 x 1200 @ 60 Hz
DVI	—
HDMI	Up to 4096 x 2160 @30Hz (HDMI 1.4)
Display Port	—
LVDS	—
eDP	—
Backlight Control	—
Environment & Power & ME	
Battery	Lithium battery
Power Requirement	ATX
Operation Temperature	32°F ~140°F (0°C ~ 60°C)
Storage Temperature	-40°F ~185°F (-40°C ~85°C)
Operation Humidity	0%~90%RH, non-condensing
Certificate	CE & FCC
Form Factor	Mini-ITX: 6.7" x 6.7" (170mm x 170mm)
Weight	1.1 lb (0.5 kg)
MTBF (Hours)	—

### Rear Panel I/O Ports

USB	USB 3.2 Gen 2 (10 Gbps) x 4, USB 2.0 x 2
Display I/O	VGA x 1, HDMI x 1
Audio I/O	Mic-in x 1, Line-out x 1
LAN I/O	LAN (RJ-45) port x 4
Serial Port	—
PS/2 Port	—
Others	—


### Internal I/O Connectors

Storage	SATA3.0 (6.0Gb/s) x 2, M.2 M-key (22 x 80mm) at bottom side x 1(SATA only)
USB	USB 2.0 (2 x 5-pin, 2.00mm) x 1 ports support additional 2 USB
Display I/O	—
Audio I/O	AAFF x 1, Speaker x 1
Serial Port	Boxer header for COM (RS-232/422/485) x 1 Boxer header for COM (RS-232) x 1
PS/2 Port	—
Parallel Port	—
DIO	Digital I/O box header x 1
FAN	4-pin CPU Fan connector x 1, 4-pin Chassis Fan connector x 1
Power	—
Others	Front Panel connector x 1 Chassis Intrusion x 1 Buzzer onboard x 1 CMOS jumper x 1
OS	
OS Support	Windows® 10 64-bit, Linux Ubuntu 18.04. 64-bit

## Packing List


- SATA Cable
- I/O Shield
- MIX-Q370A1

### Block Diagram



### Dimension

Unit: mm



### Ordering Information

Part number	CPU	RAM	Fan/Fanless	Display	Storage	LVDS	LAN	USB	RS-232	RS-232/422/485	Expansion Slot	Power	TPM	Temp.
MIX-Q370A1-A10-4L	Socket	SODIMM x 2	Fan	VGA, HDMI	SATA3 x2, M.2(M-key)	—	GbE x 4	USB2.0 x 4 USB 3.2 Gen 2 x 4	1	1	PCIe3.0[x16] x 1, M.2(E-Key) x 1	ATX	—	0~60°C
MIX-Q370A1-A10-2L	Socket	SODIMM x 2	Fan	VGA, HDMI	SATA3 x2, M.2(M-key)	—	GbE x 2	USB2.0 x 4 USB 3.2 Gen 2 x 4	1	1	PCIe3.0[x16] x 1, M.2(E-Key) x 1	ATX	—	0~60°C

### Optional Accessories

Part Number	Description
1759200172	CPU Cooler (2-Ball, Screw with Retention Plate)
175921156B	CPU Cooler (2-Ball, Push-pin Type)
COOLER -65W-01	CPU Cooler
1709100201	USB 2.0 Cable (10P, 200mm, p=2.00mm, w/bracket)
1701100206	COM Cable (200mm, p=2.00mm)
1700100491	USB 2.0 Cable (10P, 490mm, p=2.00mm)
1709050201	USB 2.0 Cable (5P, 220mm, p=2.00mm)