



SSF/SSH2203-Y

22" LCD, LED backlight, 500nits, FHD(1920x1920)

The **SSF/SSH2203-Y** is a 22 inch color TFT-LCD display with special aspect ratio 1:1 and wide resolution 1920 x 1920. It is Litemax's Spanpixel series product which designed for high brightness with power efficiency LED backlight. It provides LCD panel with specific aspect ratios and sunlight readable for digital signage, public transportation, exhibition hall, department store, and vending machine.

Key Features

- Sunlight Readable
- Aspect ratio 1:1
- LED Backlight
- Low Power Consumption
- Slim Bezel
- Wide viewing angle 178°(H)~178°(V)



Specifications

Model Name	SSF/SSH2203-Y
Description	22" TFT LCD, 500nits LED backlight , 1920x1920
Screen Size	22"
Display Area (mm)	394.56(H) x 394.56(V)
Brightness	500 cd/m ²
Resolution	1920x1920
Aspect Ratio	1 : 1
Contrast Ratio	650 : 1
Pixel Pitch (mm)	0.2055(H) x 0.2055(V)
Pixel Per Inch (PPI)	123
Viewing Angle	178°(H),178°(V)
Color Saturation (NTSC)	80%
Display Colors	16.7M
Response Time (Typical)	8ms
Panel Interface	LVDS
AD Board Input Interface	Dual-DVI, HDMI, DP
Input Power	DC12V
Power Consumption	29.6W, 35.8W (with AD board)
OSD Key	5 Keys (Power Switch, Menu, +, Exit, -)
OSD Control	Brightness, Color, Contrast, Auto Turing, H/V Position...etc
Dimensions (mm)	409.56x409.56x12.6
Bezel Size(U/B/L/R)	5.5/5.5/5.5/5.5 mm
Weight (Net)	2.5Kg
Operating Temperature	0 °C ~ 50 °C
Storage Temperature	-20 °C ~ 60 °C

SSF= Panel + LED Driving Board

SSH= Panel + LED Driving Board + AD Control Board





Specifications are subject to change without notice.
 All brands or product names are trademarks or registered trademarks of their respective companies.

Mechanical Drawing

Outline Dimensions

Unit:mm





MOUNTING HOLE	
A	M3 MOUNTING HOLE (8X) DP=3,5mm MAX SCREW
B	M3 PCB FIX HOLE (4X) DP=3,5mm MAX SCREW

Pin No.	Symbol	Description
1	IRLED1	LED current sense for string1
2	IRLED2	LED current sense for string2
3	VLED	LED power supply
4	VLED	LED power supply
5	IRLED3	LED current sense for string3
6	IRLED4	LED current sense for string4



Ordering Information

Part Number	Description
SSF2203-YNN-A01	22",500nits,1920x1920,LID22C,5in1,V1
SSH2203-YNN-M01	22",500nits,1920x1920,LID22C,AD9131DHP,DC12V,5in1,V1

Optional Accessories

Part Number	Description
840612031101	ADAPTER.12V.3.33A.40W.G99-KPL040F-N051.DC Plug 2.1*5.5,P
810618301010	CABLE.POWER.AC.1830mm USA type
810618301090	CABLE.POWER.AC,1830mm Europe type
810618301050	CABLE.POWER.AC.1830mm UK type
810618301170	CABLE.POWER.AC,1830mm Australia type
810618301031	CABLE.POWER.AC.1830mm Japan type

Customer request

Touch	SCT (Single-Touch), PCT (Multi-Touch)
Glass	Tempered glass, AR coating.....